

2850MAX 1" D-handle Impact Wrench

Recommended Headlines:

**POWERED UP. NOT WEIGHED DOWN.
POWER IS MANDATORY. WEIGHT, YOU CAN DO WITHOUT.**

Recommended Copy:

Tackling 18 wheels takes a tool that won't quit. Introducing the 2850MAX 1" D-handle Impact Wrench—our fiercest 1" wrench—engineered to make quick work of big jobs like semi, bus and tractor tires. This tool has been made lighter, pushed harder and worked longer to make sure it can handle repeated demands without sacrificing power. Every time you need extreme torque, this lightweight boss can get the job done.

Graphic Callout (Optional):

Our most powerful 1" Vehicle Repair impact wrench yet.

Value Propositions:

Power: Nothing matters more than torque when you're up against massive jobs. The 2850MAX is our fiercest 1" wrench yet, loaded with extreme power that lasts as long as you need and continuously delivers over time.

Durability: Steel-tough to its core, this heavy-duty impact wrench has been run harder and pushed farther to make sure it can withstand what you throw at it. Because when it comes to REAL WORK, downtime is not an option.

Ergonomics: We reduced the tool's weight without sacrificing what matters most—torque. The 2850MAX is also ergonomically designed for less fatigue.

ADDITIONAL KEY FEATURES

- Solid steel impact mechanism: Deliver 2,100 ft- lbs of torque
- Highly engineered design: Delivers the power you need over the life of the tool
- Steel core design: Nothing's been proven to last longer
- Chemical resistant housing & steel core: Stands up to drops and harsh work environments
- Lightweight: 25% lighter than the industry's leading 1" wrench
- 360° adjustable handle: The side handle rotates fully around the tool as the job demands
- Swivel hose connection: Keeps cords from getting tangled so you can move freely around the garage
- 6" anvil extension: Increases accessibility in hard to reach places

Recommended Specs:

Model	Drive Size, Type	Max Forward Torque ft.-lb. (Nm)	Max Reverse Torque ft.-lb. (Nm)	BPM	Free Speed (rpm)	Weight lb (kg)	Length in. (mm)	Sound Level dB(A)
2850MAX	1"	2000 (2715)	2100 (2850)	770	5500	19.43 (8.8)	13.1 (334)	96.7
2850MAX-6	1" - 6 inch	2000 (2715)	2100 (2850)	770	5500	21.58 (9.8)	19.1 (486)	96.7



**2850MAX 1" D-handle
Impact Wrench**



**2850MAX-6 1" D-handle
Impact Wrench
(Extended anvil)**